

HEAT APPLIED REFLECTIVE FILM

902-HA

Premium Heat Applied Retroreflective Film

Premium heat-applied silver reflective film for all EN ISO 20471 garment types.

TECHNICAL SPECIFICATIONS

APPLICATION

Heat Applied -- Heat Press Required

COLOUR

Silver (Light Silver Appearance)

REFLECTIVITY

330 cd/lx-m²

AVAILABLE WIDTHS

6 mm | 50 mm | 500 mm (50 cm)

ROLL LENGTH

200 m/roll (50 mm) | 100 m/roll (6 mm) | 50 m/roll (50 cm)

CARTON QTY

1,200 m (50 mm) | 8,000 m (6 mm) | 100 m (50 cm)

WASH

50 x Domestic @ 60 C

FLAME RETARDANT

No

STANDARDS

ANSI 107 | EN ISO 20471 | CSA Z96-15

IDEAL APPLICATIONS

Hi-Vis Garments · Safety Jackets · Garment Branding & Graphics

CARTON DIMENSIONS / WEIGHT

6 MM

Carton Dimensions: 48 x 27 x 31 cm Carton Weight: 20.5 kg

50 MM

Carton Dimensions: 51 x 24 x 31 cm Carton Weight: 21 kg

50 CM

Carton Dimensions: 111 x 20 x 22 cm Carton Weight: 33 kg

